

# GP100 / GP250

## Electronic General Purpose Bench Scale



*Replaces the traditional mechanical scales*

- **Battery Operated**– Uses one 9 volt battery
- **Weight Hold Key**– Locks the weight reading when a large package blocks the display
- **Portable**– Attached handle allows for easy transport
- **Discrete Switch Keyboard Technology**– Unique key button design to ensure reliability and longevity
- **Internal Backlit Display**– Display is integrated into the scale base. 25 mm / 1" high backlit digits allow for easy visibility.
- **Electro-Mechanical Design**– Ensures greater accuracy even at higher weight capacities

# GP100 / GP250 Electronic General Purpose Bench Scale

## Features

**Construction:** 22 gauge steel with ribbed base designed to protect against damage to the scale

**Display:** Four large 25 mm / 1" H digits, backlit LCD display

### Keyboard Functions:

**Hold** Freezes weight on the display only when a weight of 3 lbs or more is placed on the scale

**TARE** Removes weight of empty container or item placed on the scale to obtain a net weight

**UNITS** Scrolls between kilograms and pounds  
Turns scale on or off and returns scale to zero weight

### Indicator Displayed Messages:

**L0** Battery is weak  
After 5 minutes scale will turn off

### Auto Zero Tracking:

Includes AZT (Auto Zero Tracking) at 0.5 or manual push button to reestablish zero reference when displayed weight is less than 2% of capacity

**Overload Capacity:** Capable of withstanding 200 kg or 400 lb of weight without damaging the scale

**Auto Shutdown:** To conserve battery life the display will shutdown after 2 minutes of non-use. Can be configured via the keypad for Off, 2 or 4 minutes.

## Specifications

<u>Capacity (kg)</u>	<u>Capacity (lb)</u>
45 x 0.1 kg	100 x 0.2 lb
110 x 0.2 kg	250 x 0.5 lb

**Accuracy:**  $\pm 3$  displayed divisions

### Dimensions:

**Scale:** 278 mm (L) x 318 mm (W) x 56 mm (H)  
10.95" (L) x 12.50" (W) x 2.20" (H)

**Shipping Carton:** 339 mm (L) x 318 mm (W) x 76 mm (H)  
13.35" L x 13.5" W x 3" H

**Power:** Internal Battery: One 9 volt (not included)  
AC Adapter: 9 VDC @ 200 mA (included)

**Operating Temperature:** 5° C to 40° C / 42° F to 104° F

**Agency Approvals:** UL/CUL power adapter, FCC

**Scale Weight:** 3 kg / 6 lb

**Shipping Weight:** 4 kg / 8 lb



a division of Avery Weigh-Tronix, LLC

### Brecknell

1000 Armstrong Dr., Fairmont, MN 56031  
Toll free: 800-637-0529, Tel: 507-238-8702  
Fax: 507-238-8271  
e-mail: sales@brecknellscscales.com  
www.brecknellscscales.com



### Brecknell

Foundry Lane, Smethwick  
West Midlands B66 2LP UK  
Tel: +44 (0) 845 246 6717  
Fax: +44 (0) 845 246 6718  
Email: sales@brecknellscscales.co.uk  
www.brecknellscscales.co.uk

